






注: 本资料禁止传输、复制、编辑或存档, 以及用其内容进行复制或

REV	ECN NO.	CONTENT	CHK	DATE



Pcb Layout

NOTES1:
UL Standard

1	Use group	B	C	D
	Rated Current	8A	/	8A
	Rated Voltage	300V	/	300V

IEC Standard

1	Pollution Degree	3	2	2
	Overvoltage Category	III	III	II
	Rate Impulse Voltage(KV)	2.5KV	2.5KV	2.5KV
	Rate Voltage(V)	160V	160V	320V
	Rate Current(A)	8A	8A	8A

NOTES2:
1.Housing: PA66 (UL94V-0)
2.Clamp: Copper alloy (Sn Plated)

NOTES3:
1.Pitch: 3.81mm Poles: 02-24P
2.Stripping length: /
3.Operating temperature: -40℃~+105℃
4.RoHS Compliance

How to order
MX15EDGA - 381 - XXP - XXXX - X - X
产品型号 间距 颜色: 极数 01:常规颜色
灰色:GY 棕色:OE 02-99:
蓝色:BU 红色:RD 定制颜色
黑色:BK 透明色:TT
绿色:GN 黄色:YW
白色:WE
Cu:铜
Fe:铁
A-Z其他定制

Pitch Range In mm	Nominal Dimension Range In mm					
	Over 6 TO 10	Over 10 TO 24	Over 30 TO 60	Over 60 TO 100	Over 100 TO 150	Over 150
±0.15	±0.20	±0.30	±0.30	±0.50	±0.70	±1.00
						±1.30
						±2°

ITEM	NAME OF PART	NO OF PART	Q'TY	MATERIAL	NOTE
DWG	CHK	DATE	UNITS	MM	SHEET/OF 1/1
CHK	DATE	SCALE	1:1	A4	
APP	DATE	NAME			
		MX15EDGA-3.81-XXP			

慈溪市迈旭电子有限公司
CIXI MAIXU ELECTRONICS CO.,LTD.